

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Name : METOSSET CONCRETE REPAIR COMP A
 Type of product : A Chemical anchoring application
 Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use
 Use of the substance/mixture : A Chemical anchoring application
 Function or use category : Building and construction work

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

www.timbabuildnz.com
 Timbabuild NZ Ltd (Distributor) / (Unit 3) 6 Hoffs place,
 Kenepuru, Porirua, 5022

Email. timbabuildnz@gmail.com

1.4. Emergency telephone number

Emergency number Emergency Tel. 0800 222 214

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification of the substance or mixture

This product contains less than 1% respirable crystalline silica, so it does not require classification

Adverse physicochemical, human health and environmental effects

Causes skin irritation. Causes serious eye irritation.

Hazardous Substances (Hazard Classification) Notice 2020.:

This product was classified in accordance with Hazardous Substances (Hazard Classification) Notice 2020.

Skin corrosion/irritation, Category 2 H315
 Serious eye damage/eye irritation, Category 2 H319
 Full text of H- and EUH-statements: see section 16

2.2. Label elements

Label elements, including precautionary statements: Hazardous Substances (Hazard Classification) Notice 2020.:

Hazard pictograms (CLP)



GHS07

Signal word (CLP)

: Warning

METOSET CONCRETE REPAIR COMP A

Safety Data Sheet

According to Consolidated Hazardous Substances (Safety Data Sheets) Notice 2017

Hazard statements (CLP)	: H315 - Causes skin irritation. H319 - Causes serious eye irritation.
Precautionary statements (CLP)	: P264 - Wash hands, forearms and face thoroughly after handling. P280 - Wear protective clothing, eye protection, face protection. P302+P352 - IF ON SKIN: Wash with plenty of soap and water. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P332+P313 - If skin irritation occurs: Get medical advice/attention. Substances that contribute to the classification 2,2'-[(4-methylphenyl)imino]bisethanol CAS: 3077-12-1 . May produce an allergic reaction.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component	
2,2'-[(4-methylphenyl)imino]bisethanol	The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
VINYL TOLUENE.	CAS-No.: 25013-15-4	>3 - <10	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
2,2'-[(4-methylphenyl)imino]bisethanol	CAS-No.: N/A EC-No.: 911-490-9 REACH-no: 01-2119979579-10	< 1	Replace with cute Tox. 4: H302; Aquatic Chronic 3: H412; Eye Dam. 1: H318; Skin Sens. 1: H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.

METOSET CONCRETE REPAIR COMP A

Safety Data Sheet

According to Consolidated Hazardous Substances (Safety Data Sheets) Notice 2017

First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam.
------------------------------	----------------------------------

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Mechanically recover the product.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store in a well-ventilated place. Keep cool.
--------------------	--

METOSET CONCRETE REPAIR COMP A

Safety Data Sheet

According to Consolidated Hazardous Substances (Safety Data Sheets) Notice 2017

7.3. Specific end use(s)

Building and construction work.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Vinytoluene CAS: 25013-15-4	TWA	50 ppm	242 mg/m ³
	STEL	100 ppm	483 mg/m ³

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Chemical resistant gloves (according to European standard ISO 374-1 or equivalent)

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves, Reusable gloves	Nitrile rubber (NBR), Butyl rubber, Viton® II	6 (> 480 minutes)	0.4	As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.	EN ISO 374

METOSET CONCRETE REPAIR COMP A

Safety Data Sheet

According to Consolidated Hazardous Substances (Safety Data Sheets) Notice 2017

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. EN141

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Colour	: Various.
Appearance	: Paste.
Odour	: Characteristic odour.
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Lower explosion limit	: Not applicable
Upper explosion limit	: Not applicable
Flash point	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: Not available
pH	: Not available
pH solution	: Not available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: > 100000 cP
Solubility	: Material insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 1.5 hPa
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 1.71
Relative vapour density at 20°C	: Not applicable
Particle size	: Not available

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content	: 160 g/l
Additional information	: Solid suspension - classified as non-flammable according to results from Test N.1 test method for readily combustible solids.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

METASET CONCRETE REPAIR COMP A

Safety Data Sheet

According to Consolidated Hazardous Substances (Safety Data Sheets) Notice 2017

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

VINYL TOLUENE. (25013-15-4)

LD50 oral rat	3680 mg/kg
---------------	------------

LD50 dermal	4490 mg/kg
-------------	------------

2,2'-[(4-methylphenyl)imino]bisethanol CAS: 3077-12-1

LD50 oral rat	619 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: EU Method B.1 (Acute Toxicity (Oral)), Remarks on results: other:, 95% CL: 305 - 1256
---------------	---

LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity), Guideline: other:
-----------------	--

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

VINYL TOLUENE. (25013-15-4)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified

VINYL TOLUENE. (25013-15-4)

NOAEC (inhalation, rat, gas, 90 days)	60 ppm Animal: rat, Remarks on results: other:
---------------------------------------	--

Aspiration hazard : Not classified

11.2. Information on other hazards

No additional information available

METOSET CONCRETE REPAIR COMP A

Safety Data Sheet

According to Consolidated Hazardous Substances (Safety Data Sheets) Notice 2017

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Not rapidly degradable

VINYL TOLUENE. (25013-15-4)	
LC50 - Fish [1]	5.2 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	1.3 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	4.3 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	2.6 mg/l Source: ECHA
NOEC chronic fish	2.6 mg/l

2,2'-[(4-methylphenyl)imino]bisethanol CAS: 3077-12-1	
LC50 - Fish [1]	100 mg/l
EC50 - Crustacea [1]	48 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	100 mg/l
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

VINYL TOLUENE. (25013-15-4)	
Partition coefficient n-octanol/water (Log Pow)	3.35 Source: ECHA

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Regulations related to waste management

Legislation related to waste management:
Consolidated Imports and Exports (Restrictions) Prohibition Order (No 2) 2004 Consolidated Hazardous Substances (Disposal) Notice 2017

METOSET CONCRETE REPAIR COMP A

Safety Data Sheet

According to Consolidated Hazardous Substances (Safety Data Sheets) Notice 2017

SECTION 14: Transport information

This product is not regulated for transport.

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated for transport				
14.2. UN proper shipping name				
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.3. Transport hazard class(es)				
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.4. Packing group				
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.5. Environmental hazards				
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not regulated.

Transport by sea

Not regulated.

Air transport

Not regulated.

Inland waterway transport

Not regulated.

Rail transport

Not regulated.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question:

15.1.1.

Substances listed in the Montreal Protocol: Non-applicable

-Substances listed in the Rotterdam Convention: Non-applicable

-Substances listed in the Stockholm Convention: Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product. Relevant regulatory requirements: Health and Safety at Work (Hazardous Substances) Regulations 2017 Health and Safety at Work Act 2015 Consolidated Hazardous Substances (Labelling) Notice 2017 Consolidated Hazardous Substances (Packaging) Notice 2017 Consolidated Hazardous Substances (Hazardous Property Controls) Notice 2017 Consolidated Hazardous Substances (Importers and Manufacturers) Notice 2015 HSNO: HSR002670 Surface Coatings and Colourants (subsidiary Hazard) Group Standard 2020

METOSET CONCRETE REPAIR COMP A

Safety Data Sheet

According to Consolidated Hazardous Substances (Safety Data Sheets) Notice 2017

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer :
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit

METOSSET CONCRETE REPAIR COMP A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H412	Harmful to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.